

**SCHOOL GUARD GLASS™ SECURITY GLAZING  
I-1/16" LAMINATED INSULATED GLASS UNIT  
SG4 with Vitro Solarban 70 Low-e**

ARGON GAS FILLED

PRODUCT #: SGG-IG17.SG4.SB70-T4.SP6-ARG

**DESCRIPTION:**

An attack resistant insulated glass unit with an outboard pane of 1/4" Vitro clear tempered glass coated with Solarban 70 low-e on surface #2. The SG4™ portion is a laminated glass composite product consisting of outer layers of glass with a custom security strengthened substrate core. It is specifically designed to slow down intruders but is not bullet resistant to certain ballistic threats. When shot, it will not shatter like ordinary tempered glass and is far stronger than laminated glass of glass reinforced with security film. SG4™ remains in the frame blocking the intruder from entry.

**FEATURES:**

- SG4 attack resistant
- Insulated glass unit
- Argon gas filled
- Vitro Solarban 70 low-e

CONSTRUCTION:	PERFORMANCE DATA:										
<i>Attack side / Outboard / Exterior</i>	<p>Max Dimension: 48" x 96" (standard) 72" x 144" (special order)</p> <hr/> <p>Nominal Thickness: 1-1/16"</p> <hr/> <p>Weight: 7.21 Lbs. / Square Foot</p> <hr/> <p>Attack Rating: 5-aa I rated for 6 minutes</p>										
1/4" Tempered Clear Glass w/ Solarban 70 Low-e (#2)	<table border="1"> <thead> <tr> <th>U-VALUE</th> <th>SHGC</th> <th>VISUAL LIGHT TRANS.</th> <th>SHADING COEFFICIENT</th> <th>RELATIVE HEAT GAIN</th> </tr> </thead> <tbody> <tr> <td align="center">.24</td> <td align="center">.27</td> <td align="center">.62</td> <td align="center">.31</td> <td align="center">65.17</td> </tr> </tbody> </table> <p align="center"><small>*Calculated using LBL Window Software v7.7.1</small></p>	U-VALUE	SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN	.24	.27	.62	.31	65.17
U-VALUE		SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN						
.24	.27	.62	.31	65.17							
3/8" Argon Gas Filled Space											
7/16" Proprietary School Guard SG4											
<i>Protection side / Inboard / Interior</i>											

**COMPLIANCES:**

- ASTM C1036 – Standard Specification – Flat Glass
- ASTM E2190 – Standard Specification for IGU Performance
- ASTM C1172 – Standard Specification for Laminated Architectural Flat Glass
- ANSI Z97.1 - Safety Materials Used in Buildings
- CPSC 16 CFR 1201

**INSTALLATION SPECIFICATIONS:**

Follow basic installation specifications detailed by window/door framing vendor and School Guard Glass must also be installed with wet structural glazing techniques outlined by separate SGG install specifications.

**ADD-ON OPTIONS & ADDITIONAL INFO:**

*Some additional combination options may include:*

- Monolithic versions
- Various spacers/sizes
- Spandrel glass
- Smart Glass – instantly switchable privacy glass
- Air or argon gas fills
- Tinted glass
- Colored Interlayers
- Smart Designs - decorative options inside glass
- Various low-e coatings
- Textured glass
- Logos or signage in glass
- Custom designs & make-ups

Contact a School Guard Glass or AIT representative for all possible options, or custom makeups.

**School Guard Glass - +1 (844) 744-5277 - [www.schoolguardglass.com](http://www.schoolguardglass.com)**

v2021.04.14-PTH