

SCHOOL GUARD GLASS™ SECURITY GLAZING

1-3/16" INSULATED GLASS UNIT
SG5 with Vitro Solarban 60 Low-e
 ARGON GAS FILLED

PRODUCT #: SGG-IG19.SG5.SB60-4T.SP8-ARG

DESCRIPTION:

An attack resistant insulated glass unit with 1/4" clear tempered glass coated with Vitro Solarban 60 low-e as the outer lite, and SG5 on the inner lite, separated by a 1/2" spacer. SG5 is a laminated glass product composed with outer layers of glass with a custom security strengthened substrate core. It is specifically designed to slow down intruders but is not bullet resistant to certain ballistic threats. When shot, it will not shatter like ordinary tempered glass and is far stronger than laminated glass of glass reinforced with security film. SG5 remains in the frame blocking the intruder from entry.

FEATURES:

- Attack resistant
- SG5 security
- Insulated glass unit with Argon gas fill
- SB60 low-e
- Clear glass

CONSTRUCTION:	PERFORMANCE DATA:										
<i>Attack side / Outboard / Exterior</i>	<p>Max Dimension: 48" x 96" (standard)</p> <p>Thickness: 1-3/16</p> <p>Weight: 7.63 Lbs. / Square Foot</p>										
1/4" Clear Tempered Glass w/ Vitro Solarban 60 low-e (#2)	<p>Attack Rating: 5-aa I rated for 12 minutes ASTM F1233 Class I.4</p>										
1/2" Argon Gas Filled Space	<table border="1"> <thead> <tr> <th>U-VALUE</th> <th>SHGC</th> <th>VISUAL LIGHT TRANS.</th> <th>SHADING COEFFICIENT</th> <th>RELATIVE HEAT GAIN</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">.23</td> <td style="text-align: center;">.38</td> <td style="text-align: center;">.66</td> <td style="text-align: center;">.44</td> <td style="text-align: center;">90.22</td> </tr> </tbody> </table>	U-VALUE	SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN	.23	.38	.66	.44	90.22
U-VALUE	SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN							
.23	.38	.66	.44	90.22							
7/16" Proprietary School Guard SG5	<i>*Calculated using LBL Window Software v7.7.1</i>										
<i>Protection side / Inboard / Interior</i>											

COMPLIANCES:

- ASTM C1036 – Standard Specification – Flat Glass
- ASTM C1172 – Standard Specification for Laminated Architectural Flat Glass
- ASTM E2190 – Standard Specification for IGU Performance
- ANSI Z97.1 - Safety Materials Used in Buildings
- CPSC 16 CFR 1201

INSTALLATION SPECIFICATIONS:

Follow structural wet glaze impact glass installation specifications as determined by hurricane resistant framing vendor. Products with School Guard Glass must also be installed with wet structural glazing techniques outlined by separate SGG installation specifications.

ADD-ON OPTIONS & ADDITIONAL INFO:

Some additional combination options may include:

- Monolithic versions
- Air or argon gas fills
- Various low-e coatings
- Various spacers/sizes
- Tinted glass
- Textured glass
- Spandrel glass
- Colored Interlayers
- Logos or signage in glass
- Smart Glass – instantly switchable privacy glass
- Smart Designs - decorative options inside glass
- Custom designs & make-ups

Contact a School Guard Glass or AIT representative for all possible options, or custom makeups.

School Guard Glass - +1 (844) 744-5277 - www.schoolguardglass.com

v2023.03.29.PTH