



PRODUCT DATA SHEET

SMARTGARD SECURITY GLAZING

CP750

3/4" CONTAINMENT GRADE POLYCARBONATE COMPOSITE

PRODUCT #: CP750

DESCRIPTION:

A three-ply laminate composite constructed with polycarbonate core layers bonded together with adhesive interlayers. The exposed surface on the interior and exterior is an abrasion polycarbonate.

FEATURES:

- Attack resistant
- Ballistic
- Abrasion resistant surfaces

CONSTRUCTION:	PERFORMANCE DATA:										
<i>Attack side / Outboard / Exterior</i>	Max Dimension: 72" x 96" (standard)										
.118" Polycarbonate Layer (Abrasion resistant)	Thickness: Nominal: 3/4" • Actual: 0.786"										
.025" Urethane Bonding Interlayer	Thickness Tolerance: 0.760" to 0.812"										
.500" Polycarbonate Layer	Weight: 4.98 Lbs. / Square Foot										
.025" Urethane Bonding Interlayer	Forced Entry & Containment Rating: ASTM F1915 Grade I (60 min attack) HP White TP-0500.03 Level 3 Seq. 26										
.118" Polycarbonate Layer (Abrasion resistant)											
<i>Protection side / Inboard / Interior</i>											
	<table border="1"> <thead> <tr> <th>U-VALUE</th> <th>SHGC</th> <th>VISUAL LIGHT TRANS.</th> <th>SHADING COEFFICIENT</th> <th>RELATIVE HEAT GAIN</th> </tr> </thead> <tbody> <tr> <td>.77</td> <td>.78</td> <td>.78</td> <td>.90</td> <td>189.62</td> </tr> </tbody> </table>	U-VALUE	SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN	.77	.78	.78	.90	189.62
U-VALUE	SHGC	VISUAL LIGHT TRANS.	SHADING COEFFICIENT	RELATIVE HEAT GAIN							
.77	.78	.78	.90	189.62							
	<i>*Calculated using LBL Window Software v7.7.1</i>										

COMPLIANCES:

- CPSC 16 1201 (Category I and II)
- ANSI Z97.1 - Safety Materials Used in Buildings
- Made from UL 972 Listed Polycarbonate Sheet

INSTALLATION SPECIFICATIONS:

AIT strongly suggests the use of a suitable structural security framing with an appropriate protection rating. Allow for a minimum of a (1) inch edge engagement in the frame with sufficient rabbet depth to allow for expansion (approximately 1/16"/FT). Only use sealants and gaskets that are compatible with polycarbonate.

Remove protective masking when installation is complete and before prolonged exposure to sunlight, weather, and moisture.

ADD-ON OPTIONS & ADDITIONAL INFO:

Some additional combination options may include:

- One-way mirror
- Insulated glass units with air or argon gas fills
- Various low-e glass
- Glass cladding (GCP)
- Varied thicknesses
- Tinted appearance
- Machining: shapes, notches, or holes
- Textured glass
- Colored Interlayers
- Logos or signage in-between layers
- Smart Glass – instantly switchable privacy glass
- Smart Designs - decorative options inside glass
- Custom designs & make-ups
- Installation consultation or services

Contact an AIT representative for all possible options, or custom makeups.

v2020.05.04.PTH